

# ZU860

Spectacular image quality, low maintenance and ultimate reliability



- **Bright 9600 lumen laser WUXGA DLP projector**
- **Up to 30,000 hours maintenance-free laser light source**
- **Dust resistant – independently tested, IP5X certified for total reliability**
- **Installation flexibility – 7x lens options including ultra short throw and dome lens**

The ZU860 combines superior colour with exceptional brightness consistency. The innovative laser technology delivers ultimate colour performance whilst the DuraCore laser light source maintains exceptional brightness consistency.

Delivering up to an astonishing 30,000 hours, this projector achieves superior colour rendition.

Designed for even the most complex professional installations, the ZU860 offers seven interchangeable lens options including an ultra short throw lens and single-projector dome lens for ultimate flexibility.

## Specifications

EAN: 5055387662933, Colour: Black



<b>Ekran ve görüntü</b>	
Görüntü Teknolojisi	DLP™
Doğal Çözünürlük	WUXGA (1920x1200)
Parlaklık (Lümen)	9.600
ANSI parlaklığı	8.500
Kontrast Oranı	2.000.000
Kontrast Oranı (Dinamik)	6.000
Kontrast Oranı / Full (Açık-kapalı)	2.000
Doğal en boy oranı	16:10
Desteklenen en-boy oranı	4:3,16:9,16:10
Keystone Düzeltme (Yatay)	+/-20°
Keystone Düzeltme (Dikey)	+/-20°
Uniformity (Yüzde)	90
Ekran boyutu	Dependent on lens
<b>Lamba bilgisi</b>	
Işık Kaynağı	Lazer
ProjLaserSaatleri	30.000
<b>Optik</b>	
Atma oranı	Dependent on lens
ProjeksiyonMesafeMetre	Dependent on lens
Lens seçenekleri	BX-CTA16- 0.36 ~ 0.36 BX-CTA17- 0.65~0.75 BX-CTA15- 0.75 ~ 0.95 BX-CTA01- 0.95 ~ 1.22 BX-CTA06- 1.22 ~ 1.53 BX-CTA03- 1.52 ~ 2.92 BX-CTA13- 2.90 ~ 5.50 BX-CTADOME- Dome lens
<b>bağlantı</b>	
Bağlantılar	<b>Inputs</b> 2 x HDMI, 1 x VGA, 1 x DVI-D, 1 x HDBaseT, 1 x 3D senkronizasyon, 1 x 3G-SDI <b>Outputs</b> 1 x VGA, 1 x USB-A, 1 x 3D senkronizasyon <b>Control</b> 1 x 12V trigger, 1 x RS232, 1 x kablolu uzaktan kumanda, 1 x RJ45
<b>Genel</b>	
Gürültü Düzeyi Tipik (Db)	32
Gürültü Seviyesi Max (Db)	35
Bilgisayar Uyumluluğu	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
2D Uyumluluk	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
3D Uyumluluk	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Proj3DType	Full 3D
Ürün Güvenliği	Security bar, Kensington Lock
IP derecelendirme	IP5X
OSDLiang'lar	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
7/24 işlem	Yes
360 derece İşlem	Yes
Çalışma koşulları	5°C~35°C/41°F~95°F, max altitude M/0ft, max humidity 85%
Uzaktan kumanda	Kablolu ProAV uzaktan kumanda
Isı Yayımlı (Btu / Saat)	2.235
Kutuda	AAA Battery, AC power cable 3M, Lens cover, VGA cable 1.8m, User manual CD, Quick start guide
İsteğe bağlı kablolu modeller	QuickCast Bundle, QuickCast starter kit
<b>ağ</b>	
LanControl	Yes
LAN(DHCP)	Yes
<b>Güç</b>	
Güç kaynağı	100 - 240V, 50 - 60Hz
Güç Tüketimi / Watt (Beklemede)	0.5
Güç Tüketimi / Watt (Min)	300
Güç Tüketimi / Watt (Maks)	625
<b>Ağırlık ve boyutlar</b>	
Ürün Boyutları	484 x 529 x 195
Brüt ağırlık	22.6 kg
Net ağırlığı	17.6 kg

