

ZK507-W

4K UHD high brightness laser projector



- **Bright 4K UHD laser projector - 5000 ANSI lumens**
- **HDR Compatible**
- **1.6 x zoom, vertical lens shift**
- **30,000 hours maintenance-free laser light source**

tbd



Specifications

EAN: 5055387663619, Colour: White

UPC: 796435 44 445 7, Colour: White

| | |
|-------------------------------|--|
| Display/image | |
| Display technology | DLP™ |
| Resolution | UHD (3840x2160) |
| Brightness | 5,000 lumens |
| Contrast ratio | 300,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3, 16:9 |
| Displayable colors (millions) | 1073.4 |
| Horizontal scan rate | 31 ~ 135Khz |
| Vertical scan rate | 24 ~ 120Hz |
| Uniformity | 70% |
| Screen size | 26.45" ~ 302.2" diagonal |
| Lamp info | |
| Light source type | Laser |
| LASER life | 30,000 hours |
| Optical | |
| Throw ratio | 1.39:1 ~ 2.22:1 |
| Projection distance | 51.18" - 366.14" |
| Zoom | 1.6 |
| Zoom type | Manual |
| Focal length (mm) | 20.91mm~32.62mm/0.823"~1.284" |
| Lens shift | Vertical +15%, Horizontal: +/-0% |
| Native offset | 100% |
| Lens shift | Yes - {{downloads_link}} |
| Connectivity | |
| Connections | Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A Control 1 x USB-A service, 1 x RS232, 1 x RJ45, 1 x 12V trigger |
| General | |
| Noise level (typical) | 30dB |
| Noise level (max) | 32dB |
| PC compatibility | UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | UHD: 2160p(24/50/60Hz) / HDTV: 720p(50/60Hz), 1080i(50/60Hz), 1080p(24/50/60Hz) / SDTV : 480i/p, 576i/p |
| 3D compatibility | Frame packing, Side-by-Side, Top-and-Bottom |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 9 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish |
| 24/7 operation | Yes |
| Operating conditions | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% |
| Remote control | Backlit ProAV remote |
| Speaker count | 2 |
| Watts per speaker | 5W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Optional wireless models | HDCast Pro, QuickCast Bundle, QuickCast starter kit |
| Networking | |
| LAN - control | Yes |
| Power | |
| Power supply | 100V ~ 240V, 50-60Hz |
| Power consumption (standby) | <0.5W |
| Power consumption (min) | 274W |
| Power consumption (max) | 423W |
| Weight and dimensions | |
| Dimensions (W x D x H) | 19.61" x 13.03" x 6.73" |
| Gross weight | 27.34 lbs |
| Net weight | 23.24 lbs |

