

ZU506Te

High brightness professional laser projector



- **Bright WUXGA laser projector - 5500 ANSI lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K, HDR Compatible**
- **HDBaseT**

Professional life like colours and a smaller lighter chassis than ever before. 4K and HDR compatible, the ZU506Te is a low maintenance projector with extremely long-life laser technology at an impressive 5500lms.



Specifications

Display/imagen	
Tecnología de visualización	DLP
Resolución	WUXGA (1920x1200)
Brillo	5.500 lumens
ANSI Brillo	5.500 lumens
Ratio de contraste	300.000:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9,16:10
Corrección Keystone - Horizontal	+/-30°
Corrección Keystone-Vertical	+/-30°
Corrección Keystone vertical automática	Yes
Reproducción de color (milliones)	1073.4
Frecuencia de muestreo horizontal	15.375 ~ 91.146 KHz
Frecuencia de muestreo vertical	50 ~ 85 Hz (120Hz for 3D)Hz
Uniformidad	85%
Tamaño de pantalla	0.74m ~ 7.62m (29.1" ~ 300") diagonal

Info Lámpara	
Fuente de luz	Laser
Vida del LÁSER	30.000horas

Óptica	
Distancia de tiro	1.4:1 ~ 2.24:1
Distancia de proyección (m)	1m - 10m
Zoom	1.6
Tipo de zoom	Manual
Distancia focal (mm)	20.91 ~ 32.62
Lens shift	Vertical -99 ~ 107%, Horizontal: +/-0%
Offset nativo	99%
Lens shift	Yes - {{downloads_link}}

Conectividad	
Conexiones	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a / 3D , 2 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x RS232, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 12V trigger, 1 x S-Video, 1 x RJ45 Outputs 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm

General	
Nivel sonoro (típico)	28dB
Compatibilidad PC	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Seguridad	Security bar, Kensington Lock, Password protected interface
idiomas OSD / display	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operatividad 24/7	Yes
Operatividad 360°	Yes
Condiciones de funcionamiento	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Control remoto	Mando ProAV retroiluminado
Altavoces	2
Wattios por altavoz	10W
Contenido caja	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit

Networking	
LAN - control	Yes

Corriente	
Fuente de alimentación	100V ~ 240V, 50-60Hz
Consumo energético (standby)	<0.5W
Consumo energético (mín.)	190W
Consumo energético (máx.)	341W

Peso y dimensiones	
Peso	5.5kg
Dimensiones (W x D x H)	374 x 432 x 167 mm

