

# ZU720T

World's first fixed lens 7500 lumen WUXGA laser projector



- **7500 lumen fixed lens - Ultra bright for installations where high brightness is required**
- **Full lens shift - Motorized lens shift for simple set up**
- **Large zoom range - 1.8x zoom expands placement opportunities**
- **30,000 hours laser light source - Little to no maintenance for up to 30,000 hours**



The ZU720T is the world's first fixed lens 7500 lumen WUXGA laser projector. Delivering high brightness along with 4K and HDR compatibility, the ZU720T offers low maintenance and extremely long-life DuraCore laser projection technology.

## Specifications

UPC: 796435 44 431 0, EAN: 5055387663411, Colour: Black

EAN: 5055387665682, Colour: RAL



### Display/image

Display technology	DLP™
Resolution	WUXGA (1920x1200)
Brightness	7,500 lumens
Contrast ratio - dynamic	1,000,000:1
Contrast ratio - full on/off	2,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Screen size	40" ~ 300" diagonal

### Lamp info

Light source type	DuraCore Laser
LASER life	30,000 hours

### Optical

Throw ratio	1.4:1 ~ 2.5:1
Projection distance	47.24" - 649.61"
Zoom	1.8
Zoom type	Manual
Focal length (mm)	20.68mm~37.23mm/0.814"~1.466"
Lens shift	Vertical: +/-55%, Horizontal: +/-25%
Lens shift	Yes - <a href="#">[downloads_link]</a>

### Connectivity

Connections	<p><b>Inputs</b> 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync</p> <p><b>Outputs</b> 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A</p> <p><b>Control</b> 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232</p>
-------------	--

### General

Noise level (typical)	27dB
Noise level (max)	31dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP5x
OSD / display languages	23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit ProAV remote
Heat dissipation	2,013BTU/hour
Speaker count	2
Watts per speaker	10W

### Networking

LAN	Yes
-----	-----

### Power

Power consumption (standby)	0.5W
Power consumption (min)	370W
Power consumption (max)	590W

### Weight and dimensions

Dimensions (W x D x H)	19.06" x 14.8" x 7.03"
Gross weight	36.38 lbs
Net weight	28.44 lbs

