

UHD261056

Optimised 4K UHD LED display – 10 x 5.6m (452" diagonal)



- **High calibre, high-resolution indoor UHD 4K LED display**
- **Easy installation and maintenance – surface mount and front access**
- **Ultra-thin panel depth - discreet, space-saving design**
- **Best in class processing and switching – HQUltra technology**

Optoma is the one-stop solution provider for projection and LED displays with its range of 4K UHD, Full HD and custom LED displays.

The ultra-thin, 16:9 native aspect ratio 4K UHD LED displays blend discretely into any corporate, higher education, hospitality and digital signage environment.



Specifications

Screen	
Screen resolution	UHD (3840x2160)
Screen size (diagonal)	452"
Screen size	10000 x 5625
Minimum viewing distance	2.6m
Brightness (before calibration)	800 nits
Brightness (after calibration)	800 nits
Contrast	4000:1
Dimensions (W x D x H) mm	10000 x 54 x 5625
Screen processing	
Scaler-switcher	LS200T
Sender	CTRL4K
LEDs	
Pixel pitch (H x V)	2.604mm
LEDs per pixel	1R1G1B
Red wavelength (dominant)	620nm
Green wavelength (dominant)	520nm
Blue wavelength (dominant)	465nm
Pixels	
Pixel configuration	SMD 3-1
LED face colour	Black
LED size	SMD2020
Pixel resolution (width)	192 pixels/module
Pixel resolution (height)	108 pixels/module
Pixels per area	147.456 pixels/m ²
Module	
Active module width	10.000mm
Active module height	5.625mm
Standard active module area	0.1406m ²
Viewing angle - horizontal	>160°
Viewing angle - vertical	>160°
Ingress protection (front)	IP43
Ingress protection (back)	IP21
LED fixings	Front access
Storage temperature range	-10 - +50°C
Operating conditions	10 - 90 non-condensing
Operating temperature (min)	-10°C
Operating temperature (max)	50°C
Colour	
Greyscale processing depth	16 bits
Number of colours	281 (trillions)
Refresh rate	>3840 Hz
Brightness	
Brightness (before calibration)	800nits
Brightness (after calibration)	800nits
Contrast ratio	4.000
Brightness control levels	256
Power	
Input power (max)	72watts per panel
Power supply	110-240
Other	
Mechanical alignment adjustment	x/y/z (x/y/z planes)
Mitering	-90°
Mounting frame	Optional
Connectivity	
Connections	Inputs 2 x HDMI UHD 4K, 1 x HDMI FHD 1080P, 1 x DVI/HDMI, 1 x HDBaseT 4K, 1 x DisplayPort 4K, 1 x Component input via DVI-U, 1 x Composite video, 2 x 3G-SDI, 1 x VGA, 1 x RJ45 streaming, 2 x Microphone, 6 x Stereo analogue audio Outputs 1 x DVI/HDMI, 1 x HDMI UHD 4K, 1 x HDBaseT 4K, 1 x Speaker Control 1 x RS232, 1 x RJ45